


Anytime, anywhere, anyone.

MEDIANA HEARTON AED A16

FEATURES



PACE-PULSE DETECTION AND REJECTION FUNCTION. The A16 filters external pulse, like a pace-maker, and removes from the ECG reading.



FAST SHOCK DELIVERY Shock delivery within 10 seconds.



MULTILINGUAL English, Welsh and Polish - the three most spoken languages in the UK

- Analysis to unit charged and ready in 10 seconds or less
- Lightweight (weighs less than 2kg)
- Super-fast shock delivery time
- 3 language selection English, Welsh, and Polish
- Rated to IP55
- Instant switch between adult and child mode
- Battery Capacity 3000mAh/15V (200 shocks or 6hr monitoring)



OPERATION

Fully-automatic AED - no need to press the shock button. **Semi-automatic AED** - flashing button indicates 'ready for shock delivery' users press the button to deliver shock.



VOICE RECORDING

Enables a check to see what kind of on-site checks were done. When the device turns on the A16 records automatically.



PADS QUALITY CHECK


Checks connectivity, expiry date or whether they have already been used and damaged.

- Voice prompt, Action Icon (LED) Indicator, Status LCD
- Status indicator showing the battery level, self-test (pass or fail), temperature, condition and pads
- Self-test: POST (Power on Self-Test), Periodic Test (Daily, Weekly, Monthly), Pad Quality Check, BIST (Battery Insertion Self-Test)
- SD card, IR communication support
- Optional event review computer software
- Meets 2015 AHA / ERC guidelines

EASY TO USE



- Open the cover.
 - Turn on the unit



- Select language.
- Select adult or child.
- Attach pads.

OPTIONAL EVENT REVIEW SOFTWARE

The event data is stored on the SD card. When the AED doesn't have an SD card in it, or is unreadable, corrupted or damaged, the event data will be stored in the internal memory.



- Unit will analyse and charge.
 - Semi-automatic press the flashing shock button.
 - Fully-automatic shock is delivered without the need to press the button.
 - Start CPR

 COVER protects the action icon, the patient mode switch button, the power button, the select language button and the shock button.

2 LANGUAGE BUTTON

user can select the desired language among three different languages by pushing the select language button. English/Welsh/Polish.

3 PAD CONNECTOR links the pads.

PATIENT MODE SWITCH BUTTON between adult and pediatric patient by pushing the patient mode switch button.

INDICATOR LIGHTFlashes red near the relevant action icon.

- **6 INFRARED COMMUNICATION PORT** used to communicate with the PC.
- SHOCK BUTTON (SEMI-AUTO ONLY) When preparation for electric shock is completed, the shock button will flash. Push the Shock button and then the AED will deliver the shock.
- STATUS INDICATOR displays the AED, temperature, battery and the PADS status.

POWER BUTTON used to ON/OFF the power.

BATTERY user can remove or reset the battery.

- SD CARD PORT used to save the data and update the AED software.
- PADS Two-in-one electrode (Adult / Paediatric). Optional pads memory/quality version.





Q and As

- Q: Can this be used for both adults and children?
- A: Yes, and the mode can be changed using the adult to paediatric mode button on the main interface.
- Q: What languages are the unit's voice prompts in?A: There are 3 languages loaded onto the A16 in the UK, these are English, Welsh and Polish.
- Q: What temperature can the unit be stored at?
- A: Between 0° and 43° Celsius.
- Q: What IP is this rated to?
- A: The A16 unit is rated to IP55.
- Q: How many years of warranty does the unit have?
- A: The A15 and A16 both have 5 years of warranty.

- Q: What is the difference between the two types of pads?
- A: Code 2902 are the normal adult/paediatric pads. Code 2903 include a "pads quality" function, which checks whether there is a problem with the pads, for example, expired pads, damaged pads or the recommended replacement of the pads.
- Q: Does the A16 supersede the A15?
- A: No, the units are different and cater to different customers. For those that are looking for a basic AED, the A15 has a simple interface with one pre-loaded language and is therefore lower in price. The A16 has three pre-loaded languages and two pad options.
- Q: Has the A16 been drop tested?
- A: Yes, the unit has been drop tested to 0.75m on all 6 sides.

AED SPECIFICATIONS

DEFIBRILLATION ELECTRIC SHOCK	
Waveform:	Biphasic Truncated Expo

Waveform:	Biphasic Truncated Exponential (BTE) waveform
	(Impedance compensation)
Energy:	Adult: 170 to 195J (±5%)
	Paediatric: 44 to 51J (±5%)
Operating Mode:	Semi-Auto, Fully-Auto
ECG	
Lead:	II (RA, LL)
Patient Impedance:	25 to 200 ohm
Detection V/F	greater than or equal to 0.2mV
V/T	Adult: greater than or equal to 150 bpm
INDICATION	
CONTROLS	
Standard:	Power button, shock button, patient mode switch
	button, select language button.
INDICATORS	
Visible:	Action icon, Status LCD (AED, battery, temperature and
	pads status).
Audible:	Audio speaker (voice prompt, CPR indication).
	Beep (CPR indication, power on, critically low battery,
	self-test fail, alarm of abnormal operation).
PHYSICAL	
Dimensions:	286.5H x 200W x 90mmD
Weight:	Approx. 1.95kg
	(including battery, excluding pads).
Ingress Protection:	IP55
SELF TEST	
Cycle:	Every 24 hours, 1 week, 1 month.
	Power on self test, battery insertion self test.
Test Result:	Status LCD displays 'O' / 'X'.
DATA BACKUP AN	ND COMMUNICATION
Standard	Internal memory, SD card slot,
	IR communication port.
	· · · · · · · · · · · · · · · · · · ·

ACCESSORY SPECIFICATIONS

ADULT/PAEDIATRIC	
Shelf Life:	36 months from manufacture date (ref 2902)
	30 months from manufacture date (ref 2903)
Electrodes:	Disposable pads
Placement:	Adult: Anterior-lateral
	Paediatric: Anterior-posterior
Minimum active gel	area: 80cm2 +/-5%
Cable Length:	Approx. 1.8m
ENVIRONMENTAL C	CONDITIONS
Temperature:	Operation: 0 to 43°C (32 to 109.4°F)
	Storage: 0 to 43°C (32 to 109.4°F)
Relative Humidity:	5 to 95% RH (non-condensing)
BATTERY	
Туре:	LiMnO2, disposable, long-life primary cell
Voltage/Capacity:	15V, 3000 mAh
Shelf Life:	2 years from date of manufacture
	(in original packaging).
Standby Life:	5 years from date of manufacture
	(inserted in the AED)
Discharge:	A minimum of 200 shocks (except the CPR period
	between the defibrillation therapy) or more than 6 hours
	of operating time at 20°C
ENVIRONMENTAL C	CONDITIONS
Temperature:	Operation: 0 to 43°C (32 to 109.4°F)
	Storage: 10 to 25°C (50 to 77°F)
Relative Humidity:	5 to 95% RH (non-condensing)

Information correct at time of going to press. Subject to change without notice.

MEDIANA AED A16





2907 Mediana A16 HeartOn AED Soft Bag SIZE: Fits A16 and T16 UNIT MOQ:



9220

MOQ:

SIZE: 75cmHcm x 34.7cmW x 10.5cmD UNIT

TRAINER

2910 Mediana T16 HeartOn AED Trainer

MEDIANA T16 AED TRAINER

- CONTENTS Mediana HeartOn AED Trainer T16
- Operators Manual Remote Control
- Set Trainer Pads 20cmH x 28.7cmW x 9cmD
- UNIT:

MOQ;

SIZE:

SIZE:

UNIT:

MOQ; 1



2911 Mediana T16 HeartOn AED Trainer Pads

AED CONSUMABLES



AED Prep Kit in Large Black/Red Compact Aura 20.5cmH x 20cmW x 6.5cmD UNIT: MOQ: 1

2877 AED Prep Kit in Black Soft Pouch SIZE: 15.6cmH x 10.8cmW x 5.4cmD UNIT: MOQ: 1



2879

SIZE:

UNIT:



2105 SIZE: UNIT: MOQ:

AED Alarmed, Outdoor, Heated, Metal Cabinet Yellow/Alarmed/Heated Internal: 50cmH x 40cmW x 22cmD External: 37cmH x 38cmW x 17cmD 1



Universal AED Bracket Green

12.3cmH x 19cmW x 9.5cmD 1 MOQ:

Spectra A16 AED First Aid System

2780

SIZE-



www.medianadefib.co.uk

t. +44 (0) 08456 448808 e. sales@reliancemedical.co.uk w. www.reliancemedical.co.uk



Mediana HeartOn Defibrillators are distributed by Reliance Medical Limted.

